

## SAFETY DATA SHEET

# Quick Coating

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

▼ <i>Trade name:</i>	Quick Coating
<i>Product no.:</i>	1047
<i>Unique formula identifier (UFI):</i>	QST5-TG9Y-U10F-16HM

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<i>Relevant identified uses of the substance or mixture:</i>	Brightener
<i>Uses advised against :</i>	None known.

### 1.3. Details of the supplier of the safety data sheet

▼ <i>Company and address:</i>	<b>Ditec International AB</b> Dragrännan 2 S-746 50 BÅLSTA Sweden +46 10 344 74 50
<i>E-mail:</i>	info@ditecinternational.com
<i>Revision:</i>	02/02/2025
<i>SDS Version:</i>	2.0
<i>Date of previous version:</i>	29/11/2022 (1.0)

### 1.4. ▼ Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)  
General public:  
England - Dial 111 to reach NHS 111 (24 hour service)  
Scotland - Dial 112 to reach NHS 24 (24 hour service)  
Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)  
See section 4 "First aid measures".

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.  
Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

*Hazard pictogram(s):*



<i>Signal word:</i>	Warning
<i>Hazard statement(s):</i>	Flammable liquid and vapour. (H226) Harmful to aquatic life with long lasting effects. (H412)
<i>Precautionary statement(s):</i>	
▼ <i>General:</i>	If medical advice is needed, have product container or label at hand. (P101) Keep out of reach of children. (P102)
<i>Prevention:</i>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
<i>Response:</i>	In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam to extinguish. (P370+P378)
<i>Storage:</i>	Store in a well-ventilated place. Keep cool. (P403+P235)
▼ <i>Disposal:</i>	Dispose of contents/container in accordance with local regulation (P501)
<i>Hazardous substances:</i>	propan-2-ol
<i>Additional labelling:</i>	EUH208, Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.  UFI: QST5-TG9Y-U10F-16HM

### 2.3. Other hazards

▼ <i>Additional warnings:</i>	This product contains a vPvB and/or PBT substance: Octamethylcyclotetrasiloxane (PBT / vPvB) This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.
-------------------------------	---

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

Not applicable. This product is a mixture.

### 3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7 UK-REACH: Index No.: 603-117-00-0	5-10%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
Polydimethylsiloxane, diquaternary	CAS No.: 134737-05-6 EC No.: UK-REACH: Index No.:	1-3%	Aquatic Chronic 2, H411	
(2-methoxymethylethoxy)propanol	CAS No.: 34590-94-8 EC No.: 252-104-2 UK-REACH: Index No.:	1-3%		[1]

2-(2-butoxyethoxy)ethanol	CAS No.: 112-34-5 EC No.: 203-961-6 UK-REACH: Index No.: 603-096-00-8	<1%	Eye Irrit. 2, H319	[1], [3]
1,2-benzisothiazol-3(2H)-one	CAS No.: 2634-33-5 EC No.: 220-120-9 UK-REACH: Index No.: 613-088-00-6	<0.05%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.05 %) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1)	
Octamethylcyclotetrasiloxane	CAS No.: 556-67-2 EC No.: 209-136-7 UK-REACH: Index No.: 014-018-00-1	<0.05%	Flam. Liq. 3, H226 Repr. 2, H361f Aquatic Chronic 1, H410 (M=10)	[3], [5], [6], [7]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### ▼ Other information

[1] European occupational exposure limit.

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

[5] Substance is included in the Candidate List of substances of very high concern (SVHC).

[6] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[7] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

#### *General information:*

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### *Inhalation:*

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### *Skin contact:*

IF ON SKIN: Wash with plenty of water and soap. Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. If skin irritation occurs: Get medical advice/attention.

#### ▼ *Eye contact:*

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

#### ▼ *Ingestion:*

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor.

Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

*Burns:*

Rinse with water until pain stops then continue to rinse for 30 minutes.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

#### **4.3. ▼ Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

#### **Information to medics**

Bring this safety data sheet or the label from this product.

### **SECTION 5: FIREFIGHTING MEASURES**

#### **5.1. Extinguishing media**

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

#### **5.2. ▼ Special hazards arising from the substance or mixture**

Flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

#### **5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

#### **6.2. Environmental precautions**

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

#### **6.3. ▼ Methods and material for containment and cleaning up**

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

#### **6.4. Reference to other sections**

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. ▼ Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

*Recommended storage material:* Always store in containers of the same material as the original container.

*Storage conditions:* Dry, cool and well ventilated

*Incompatible materials:* Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 7.3. ▼ Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

propan-2-ol

Long term exposure limit (8 hours) (ppm): 400

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 999

Short term exposure limit (15 minutes) (ppm): 500

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 1250

(2-methoxymethylethoxy)propanol

Long term exposure limit (8 hours) (ppm): 50

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 308

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

2-(2-butoxyethoxy)ethanol

Long term exposure limit (8 hours) (ppm): 10

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 67.5

Short term exposure limit (15 minutes) (ppm): 15

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 101.2

propane-1,2-diol

Long term exposure limit (8 hours) (ppm): 150(total)

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 474(total)/10(particulates)

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.  
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

#### ▼ DNEL

##### (2-methoxymethylethoxy)propanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	121 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	283 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	37.2 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	308 mg/kg
Long term – Systemic effects - General population	Oral	36 mg/kg bw/day

##### 2-(2-butoxyethoxy)ethanol

Duration:	Route of exposure:	DNEL:
Long term – Local effects - Workers	Inhalation	67.5 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	101.2 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	6,25 mg/kg bw/day

##### Octamethylcyclotetrasiloxane

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	13 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	73 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	13 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	73 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	13 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	73 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	13 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	73 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	3.7 mg/kg bw/day
Short term – Systemic effects - General population	Oral	3.7 m mg/kg bw/day

##### propan-2-ol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	500 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day

propane-1,2-diol

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	10 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	10 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	50 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	168 mg/m <sup>3</sup>

▼ PNEC

(2-methoxymethylethoxy)propanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		19 mg/L
Freshwater sediment		70.2 mg/kg
Intermittent release		190 mg/L
Marine water		1.9 mg/L
Marine water sediment		7.02 mg/kg
Sewage treatment plant		4168 mg/L
Soil		2.74 mg/kg

2-(2-butoxyethoxy)ethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		1.1 mg/L
Freshwater sediment		4.4 mg/kg dw
Intermittent release		11 mg/L
Marine water		0.11 mg/L
Marine water sediment		0.44 mg/kg dw
Soil		0.32 mg/kg dw

Octamethylcyclotetrasiloxane

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0.44 µg/L
Freshwater sediment		0.59 mg/kg dw
Marine water		0.044 µg/L
Marine water sediment		0.059 mg/kg dw
Sewage treatment plant		10 mg/L
Soil		0.15 mg/kg dw

propan-2-ol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg
Intermittent release		140.9 mg/L
Marine water		140.9 mg/L
Marine water sediment		552 mg/kg
Sewage treatment plant		2251 mg/L

Soil		28 mg/kg
------	--	----------

propane-1,2-diol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		260 mg/L
Freshwater sediment		572 mg/kg dw
Intermittent release	-	183 mg/l
Marine water		26 mg/L
Marine water sediment		57.2 mg/kg dw
Sewage treatment plant		20000 mg/L
Soil		50 mg/kg dw

## 8.2. ▼ Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

*General recommendations:*

Smoking, drinking and consumption of food is not allowed in the work area.

*Exposure scenarios:*

There are no exposure scenarios implemented for this product.

*Exposure limits:*

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

▼ *Appropriate technical measures:*

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked. Apply standard precautions during use of the product. Avoid inhalation of vapours.

▼ *Hygiene measures:*

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

*Measures to avoid environmental exposure:*

Keep damming materials near the workplace. If possible, collect spillage during work.

## Individual protection measures, such as personal protective equipment

*Generally:*

Use only UKCA marked protective equipment.


*Respiratory Equipment:*

No specific requirements


*Skin protection:*

No specific requirements.

*Hand protection:*

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	-	-	EN374-2	

*Eye protection:*

Type	Standards	
Safety glasses with side shields.	EN166	

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Liquid
<i>Colour:</i>	Green
<i>Odour / Odour threshold:</i>	Perfume
<i>pH:</i>	5
<i>Density (g/cm<sup>3</sup>):</i>	0.98
▼ <i>Kinematic viscosity:</i>	No relevant or available data due to the nature of the product.
<i>Particle characteristics:</i>	Does not apply to liquids.

#### Phase changes

▼ <i>Melting point/Freezing point (°C):</i>	No relevant or available data due to the nature of the product.
<i>Softening point/range (°C):</i>	Does not apply to liquids.
▼ <i>Boiling point (°C):</i>	No relevant or available data due to the nature of the product.
▼ <i>Vapour pressure:</i>	No relevant or available data due to the nature of the product.
▼ <i>Relative vapour density:</i>	No relevant or available data due to the nature of the product.
▼ <i>Decomposition temperature (°C):</i>	No relevant or available data due to the nature of the product.

#### Data on fire and explosion hazards

<i>Flash point (°C):</i>	42
▼ <i>Flammability (°C):</i>	The material is ignitable.
▼ <i>Auto-ignition temperature (°C):</i>	No relevant or available data due to the nature of the product.
▼ <i>Lower and upper explosion limit (% v/v):</i>	No relevant or available data due to the nature of the product.

#### Solubility

<i>Solubility in water:</i>	Completely soluble
▼ <i>n-octanol/water coefficient (LogKow):</i>	No relevant or available data due to the nature of the product.
▼ <i>Solubility in fat (g/L):</i>	No relevant or available data due to the nature of the product.

### 9.2. Other information

*Other physical and chemical parameters:*

No data available.

▼ *Oxidizing properties:*

No relevant or available data due to the nature of the product.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

Avoid static electricity.

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 10.6. ▼ Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### ▼ Acute toxicity

Product/substance	propan-2-ol
Test method:	OECD 401
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	5840 mg/kg

Product/substance	propan-2-ol
Test method:	OECD 403
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (vapour)
Result:	>25 mg/L

Product/substance	propan-2-ol
Test method:	OECD 402
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	13900 mg/kg

Product/substance	(2-methoxymethylethoxy)propanol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>5000 mg/kg

Product/substance (2-methoxymethylethoxy)propanol  
 Species: Rabbit  
 Route of exposure: Dermal  
 Test: LD50  
 Result: 9510 mg/kg

Product/substance (2-methoxymethylethoxy)propanol  
 Species: Rat  
 Route of exposure: Inhalation  
 Test: LC50 (vapour)  
 Result: 3.35 mg/L

Product/substance 2-(2-butoxyethoxy)ethanol  
 Species: Rat  
 Route of exposure: Oral  
 Test: LD50  
 Result: >2000 mg/kg

Product/substance 2-(2-butoxyethoxy)ethanol  
 Species: Rabbit  
 Route of exposure: Dermal  
 Test: LD50  
 Result: 2764 mg/kg

Product/substance 2-(2-butoxyethoxy)ethanol  
 Species: Rat  
 Route of exposure: Inhalation  
 Test: LC50  
 Result: >29 ppm

Product/substance 2-(2-butoxyethoxy)ethanol  
 Species: Mouse  
 Route of exposure: Oral  
 Test: LD50  
 Result: 2410 mg/kg

Product/substance propane-1,2-diol  
 Species: Rat  
 Route of exposure: Oral  
 Test: LD50  
 Result: 22000 mg/kg

Product/substance propane-1,2-diol  
 Species: Rabbit  
 Route of exposure: Dermal  
 Test: LD50  
 Result: >2000 mg/kg

Product/substance propane-1,2-diol  
 Species: Rabbit  
 Route of exposure: Inhalation  
 Test: LC50 (2 hours)  
 Result: >317042 mg/m<sup>3</sup>

Product/substance 1,2-benzisothiazol-3(2H)-one  
 Species: Rat  
 Route of exposure: Dermal

Test: LD50  
Result: >2000 mg/kg

Product/substance 1,2-benzisothiazol-3(2H)-one  
Species: Mouse  
Route of exposure: Oral  
Test: LD50  
Result: 1150 mg/kg

Product/substance 1,2-benzisothiazol-3(2H)-one  
Species: Rat  
Route of exposure: Oral  
Test: LD50  
Result: 597 mg/kg

Product/substance 1,2-benzisothiazol-3(2H)-one  
Species: Rat  
Route of exposure: Dermal  
Test: LD50  
Result: >2000 mg/kg engångsdos ·

Product/substance 1,2-benzisothiazol-3(2H)-one  
Species: Rat  
Route of exposure: Oral  
Test: LD50  
Result: 1020 mg/kg ·

Product/substance Octamethylcyclotetrasiloxane  
Species: Rat  
Route of exposure: Oral  
Test: LD50  
Result: 4800 mg/kg

Product/substance Octamethylcyclotetrasiloxane  
Species: Rat  
Route of exposure: Inhalation  
Test: LC50  
Result: 36 mg/l, 4h ·

Product/substance Octamethylcyclotetrasiloxane  
Species: Rat  
Route of exposure: Dermal  
Test: LD50  
Result: >2400 mg/kg ·

### ▼ Skin corrosion/irritation

Product/substance 2-(2-butoxyethoxy)ethanol  
Test method: OECD 404  
Species: Rabbit  
Result: No adverse effect observed (Not irritating)

Product/substance Octamethylcyclotetrasiloxane  
Test method: OECD 404  
Species: Rat  
Result: No adverse effect observed (Not irritating)

### ▼ Serious eye damage/irritation

Product/substance	2-(2-butoxyethoxy)ethanol
Test method:	OECD 404
Species:	Rabbit
Result:	Adverse effect observed (Irritating)

Product/substance	Octamethylcyclotetrasiloxane
Test method:	OECD 405
Species:	Rabbit
Result:	No adverse effect observed (Not irritating)

### Respiratory sensitisation

Based on available data, the classification criteria are not met.

#### ▼ Skin sensitisation

Product/substance	2-(2-butoxyethoxy)ethanol
Test method:	OECD 406
Species:	Guinea pig
Result:	No adverse effect observed (not sensitising)

Product/substance	Octamethylcyclotetrasiloxane
Test method:	OECD 406
Species:	Guinea pig
Result:	No adverse effect observed (not sensitising)

### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

### Carcinogenicity

Based on available data, the classification criteria are not met.

### Reproductive toxicity

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### Long term effects

None known.

#### ▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

### Other information

propan-2-ol has been classified by IARC as a group 3 carcinogen.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. ▼ Toxicity

Product/substance	propan-2-ol
Species:	Fish
Duration:	96 hours
Test:	LC50

Result:	>100 mg/L
Product/substance	propan-2-ol
Species:	Algae
Duration:	8 d
Test:	LOEC
Result:	1000 mg/L
Product/substance	propan-2-ol
Species:	Daphnia, Daphnia magna
Duration:	48 hours
Test:	LC50
Result:	>100 mg/L
Product/substance	propan-2-ol
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	>100 mg/L
Product/substance	(2-methoxymethylethoxy)propanol
Species:	Fish, Poecilia reticulata
Duration:	96 hours
Test:	LC50
Result:	>1000 mg/L
Product/substance	(2-methoxymethylethoxy)propanol
Species:	Daphnia, Daphnia magna
Duration:	48 hours
Test:	EC50
Result:	1919 mg/L
Product/substance	(2-methoxymethylethoxy)propanol
Species:	Daphnia, Daphnia magna
Duration:	22 d
Test:	NOEC
Result:	0.5 mg/L
Product/substance	(2-methoxymethylethoxy)propanol
Species:	Algae, Pseudokirchneriella subcapitata
Duration:	72 hours
Test:	EC50
Result:	>969 mg/L
Product/substance	2-(2-butoxyethoxy)ethanol
Species:	Fish, Leuciscus idus
Duration:	96 hours
Test:	LC50
Result:	>100 mg/L
Product/substance	2-(2-butoxyethoxy)ethanol
Species:	Algae, Scenedesmus subspicatus
Duration:	96 hours
Test:	EC50
Result:	>100 mg/L
Product/substance	2-(2-butoxyethoxy)ethanol

Species: Daphnia, Daphnia magna  
 Duration: 48 hours  
 Test: EC50  
 Result: >100 mg/L

Product/substance propane-1,2-diol  
 Species: Fish, Oncorhynchus mykiss  
 Duration: 96 hours  
 Test: LC50  
 Result: 40613 mg/L

Product/substance propane-1,2-diol  
 Species: Daphnia, Ceriodaphnia dubia  
 Duration: 48 hours  
 Test: EC50  
 Result: 18340 mg/L

Product/substance propane-1,2-diol  
 Species: Algae, Pseudokirchneriella subcapitata  
 Duration: 96 hours  
 Test: ErC50  
 Result: 19000 mg/L

Product/substance 1,2-benzisothiazol-3(2H)-one  
 Species: Daphnia, Daphnia magna  
 Duration: 48 hours  
 Test: EC50  
 Result: 2.44 mg/L

Product/substance 1,2-benzisothiazol-3(2H)-one  
 Species: Fish  
 Duration: 96 hours  
 Test: LC50  
 Result: 0.74 mg/L

Product/substance Octamethylcyclotetrasiloxane  
 Species: Fish, Oncorhynchus mykiss  
 Duration: 96 hours  
 Test: LC50  
 Result: >0.022 mg/L

Product/substance Octamethylcyclotetrasiloxane  
 Species: Daphnia, Daphnia magna  
 Duration: 48 hours  
 Test: EC50  
 Result: 0.015 mg/L

Harmful to aquatic life with long lasting effects.

## 12.2. ▼ Persistence and degradability

Product/substance propan-2-ol  
 Conclusion: Readily biodegradable

Product/substance (2-methoxymethylethoxy)propanol  
 Result: 75%  
 Conclusion: Readily biodegradable  
 Test: OECD 301 F

Product/substance	2-(2-butoxyethoxy)ethanol
Result:	100%
Conclusion:	Readily biodegradable
Test:	OECD 301 E

Product/substance	propane-1,2-diol
Result:	81%
Conclusion:	Readily biodegradable
Test:	OECD 301 F

### 12.3. ▼ Bioaccumulative potential

Product/substance	propan-2-ol
LogKow:	0.0500
Conclusion:	No potential for bioaccumulation

Product/substance	(2-methoxymethylethoxy)propanol
LogKow:	0.0060
Conclusion:	No potential for bioaccumulation

Product/substance	2-(2-butoxyethoxy)ethanol
LogKow:	1.0000
Conclusion:	No potential for bioaccumulation

Product/substance	propane-1,2-diol
LogKow:	-1.0700
Conclusion:	No potential for bioaccumulation

Product/substance	1,2-benzisothiazol-3(2H)-one
LogKow:	1.4
Conclusion:	No potential for bioaccumulation

Product/substance	Octamethylcyclotetrasiloxane
BCF:	12400
LogKow:	5.1000
Conclusion:	Potential for bioaccumulation

### 12.4. Mobility in soil

(2-methoxymethylethoxy)propanol  
LogKoc = 0.28, High mobility potential.

### 12.5. ▼ Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

### 12.6. ▼ Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

### 12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. ▼ Waste treatment methods

Product is covered by the regulations on hazardous waste. (\*)

HP 3 - Flammable

Dispose of contents/container to an approved waste disposal plant.




Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

▼ EWC code: 07 06 04\* Other organic solvents, washing liquids and mother liquors

### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informat ion:
ADR	UN1993	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1993	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L EmS: F-E S-E See below for additional information.
IATA	UN1993	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	See below for additional information.

\* Packing group

\*\* Environmental hazards

▼ **Additional information**

This product is within scope of the regulations of transport of dangerous goods.  
 ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.  
 IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.  
 IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

**14.6. Special precautions for user**

Not applicable.

**14.7. Maritime transport in bulk according to IMO instruments**

No data available.

**SECTION 15: REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

▼ <i>Restrictions for application:</i>	No special.
<i>Demands for specific education:</i>	No specific requirements.
<i>SEVESO - Categories / dangerous substances:</i>	P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes
▼ <i>REACH, Annex XVII:</i>	2-(2-butoxyethoxy)ethanol is subject to restrictions, UK-REACH annex XVII (entry 55). Octamethylcyclotetrasiloxane is subject to restrictions, UK-REACH annex XVII (entry 70). propan-2-ol is subject to UK-REACH restrictions (entry 40). Octamethylcyclotetrasiloxane is subject to UK-REACH restrictions (entry 40).
<i>Additional information:</i>	Not applicable.
<i>Sources:</i>	The Health and Safety at Work etc. Act 1974 Regulations 2013. Control of Major Accident Hazards (COMAH) Regulations 2015. Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law. Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

**15.2. Chemical safety assessment**

No

**SECTION 16: OTHER INFORMATION**



### Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.  
H226, Flammable liquid and vapour.  
H302, Harmful if swallowed.  
H315, Causes skin irritation.  
H317, May cause an allergic skin reaction.  
H318, Causes serious eye damage.  
H319, Causes serious eye irritation.  
H336, May cause drowsiness or dizziness.  
H361f, Suspected of damaging fertility.  
H400, Very toxic to aquatic life.  
H410, Very toxic to aquatic life with long lasting effects.  
H411, Toxic to aquatic life with long lasting effects.

### ▼ Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
CAS = Chemical Abstracts Service  
CE = Conformité Européenne (European conformity)  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
CSA = Chemical Safety Assessment  
CSR = Chemical Safety Report  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EINECS = European Inventory of Existing Commercial chemical Substances  
ES = Exposure Scenario  
EUH statement = CLP-specific Hazard statement  
EuPCS = European Product Categorisation System  
EWC = European Waste Catalogue  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
GWP = Global warming potential  
IARC = International Agency for Research on Cancer (IARC)  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

### **Additional information**

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

### **The safety data sheet is validated by**

-

### **▼ Other**

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en