

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name**

Ditec Quick Coating

**Product no.**

1047

**Unique formula identifier (UFI)**

QST5-TG9Y-U10F-16HM

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Brightener

**Uses advised against**

None known.

### 1.3. Details of the supplier of the safety data sheet

**Company and address****Ditec International AB**

Ahrenbergs Brygga 32  
S-195 61 ARLANDASTAD (Stockholm)  
Sweden  
+46 10 344 74 50

**E-mail**

info@ditecinternational.com

**Revision**

29/11/2022

**SDS Version**

1.0

### 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

**Hazard pictogram(s)****Signal word**

Warning

**Hazard statement(s)**

Flammable liquid and vapour. (H226)

Harmful to aquatic life with long lasting effects. (H412)

**Safety statement(s)****General**

Keep out of reach of children. (P102)

If medical advice is needed, have product container or label at hand. (P101)

**Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

**Response**

In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam to extinguish. (P370+P378)

**Storage**

Store in a well-ventilated place. Keep cool. (P403+P235)

**Disposal**

Dispose of contents/container in accordance with local regulation  
 . (P501)

**Hazardous substances**

propan-2-ol

**Additional labelling**

EUH208, Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.  
 UFI: QST5-TG9Y-U10F-16HM

**2.3. Other hazards**

**Additional warnings**

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

**SECTION 3: Composition/information on ingredients**

**3.1. Substances**

Not applicable. This product is a mixture.

**3.2. Mixtures**

Product/substance	Identifiers	% w/w	Classification	Note
propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7 UK-REACH: Index No.: 603-117-00-0	5-10%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
Polydimethylsiloxane, diquaternary	CAS No.: 134737-05-6 EC No.: UK-REACH: Index No.:	1-3%	Aquatic Chronic 2, H411	
(2-methoxymethylethoxy)propanol	CAS No.: 34590-94-8 EC No.: 252-104-2 UK-REACH: Index No.:	1-3%		[1]
2-(2-butoxyethoxy)ethanol	CAS No.: 112-34-5 EC No.: 203-961-6 UK-REACH: Index No.: 603-096-00-8	<1%	Eye Irrit. 2, H319	[1], [3]
1,2-benzisothiazol-3(2H)-one	CAS No.: 2634-33-5 EC No.: 220-120-9 UK-REACH: Index No.: 613-088-00-6	<0.05%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.05 %) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1)	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

**Other information**

[1] European occupational exposure limit.

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

**Inhalation**

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

**Skin contact**

IF ON SKIN: Wash with plenty of water and soap. Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. If skin irritation occurs: Get medical advice/attention.

**Eye contact**

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

**Ingestion**

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

**Burns**

Rinse with water until pain stops then continue to rinse for 30 minutes.

**4.2. Most important symptoms and effects, both acute and delayed**

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

**4.3. Indication of any immediate medical attention and special treatment needed**

None known.

**Information to medics**

Bring this safety data sheet or the label from this product.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

**5.2. Special hazards arising from the substance or mixture**

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

**6.2. Environmental precautions**

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

**6.3. Methods and material for containment and cleaning up**

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

#### Recommended storage material

Always store in containers of the same material as the original container.

#### Storage temperature

Dry, cool and well ventilated

#### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

propan-2-ol

Long term exposure limit (8 hours) (ppm): 400

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 999

Short term exposure limit (15 minutes) (ppm): 500

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 1250

(2-methoxymethylethoxy)propanol

Long term exposure limit (8 hours) (ppm): 50

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 308

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

2-(2-butoxyethoxy)ethanol

Long term exposure limit (8 hours) (ppm): 10

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 67,5

Short term exposure limit (15 minutes) (ppm): 15

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 101,2

propane-1,2-diol

Long term exposure limit (8 hours) (ppm): 150(total)

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 474(total)/10(particulates)

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.  
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

#### DNEL

(2-methoxymethylethoxy)propanol

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Duration	Route of exposure	DNEL
Long term - Systemic effects - General population	Dermal	121 mg/kg bw/day
Long term - Systemic effects - Workers	Dermal	283 mg/kg bw/day
Long term - Systemic effects - General population	Inhalation	37.2 mg/m <sup>3</sup>
Long term - Systemic effects - Workers	Inhalation	308 mg/kg
Long term - Systemic effects - General population	Oral	36 mg/kg bw/day
<b>2-(2-butoxyethoxy)ethanol</b>		
Duration	Route of exposure	DNEL
Long term - Local effects - Workers	Inhalation	67.5 mg/m <sup>3</sup>
Short term - Local effects - Workers	Inhalation	101.2 mg/m <sup>3</sup>
Long term - Systemic effects - General population	Oral	6,25 mg/kg bw/day
<b>propan-2-ol</b>		
Duration	Route of exposure	DNEL
Long term - Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term - Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term - Systemic effects - General population	Inhalation	89 mg/m <sup>3</sup>
Long term - Systemic effects - Workers	Inhalation	500 mg/m <sup>3</sup>
Long term - Systemic effects - General population	Oral	26 mg/kg bw/day
<b>propane-1,2-diol</b>		
Duration	Route of exposure	DNEL
Long term - Local effects - General population	Inhalation	10 mg/m <sup>3</sup>
Long term - Local effects - Workers	Inhalation	10 mg/m <sup>3</sup>

Long term – Systemic effects - General population	Inhalation	50 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	168 mg/m <sup>3</sup>

**PNEC**

(2-methoxymethylethoxy)propanol

Route of exposure	Duration of Exposure	PNEC
Freshwater		19 mg/L
Freshwater sediment		70.2 mg/kg
Intermittent release		190 mg/L
Marine water		1.9 mg/L
Marine water sediment		7.02 mg/kg
Sewage treatment plant		4168 mg/L
Soil		2.74 mg/kg

2-(2-butoxyethoxy)ethanol

Route of exposure	Duration of Exposure	PNEC
Freshwater		1.1 mg/L
Freshwater sediment		4.4 mg/kg dw
Intermittent release		11 mg/L
Marine water		0.11 mg/L
Marine water sediment		0.44 mg/kg dw
Soil		0.32 mg/kg dw

propan-2-ol

Route of exposure	Duration of Exposure	PNEC
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg
Intermittent release		140.9 mg/L
Marine water		140.9 mg/L
Marine water sediment		552 mg/kg
Sewage treatment plant		2251 mg/L
Soil		28 mg/kg

propane-1,2-diol

Route of exposure	Duration of Exposure	PNEC
Freshwater		260 mg/L

Freshwater sediment	572 mg/kg dw
Intermittent release -	183 mg/l
Marine water	26 mg/L
Marine water sediment	57.2 mg/kg dw
Sewage treatment plant	20000 mg/L
Soil	50 mg/kg dw

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

There are no exposure scenarios implemented for this product.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

### Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

## 8.3. Individual protection measures, such as personal protective equipment

### Generally

Use only UKCA marked protective equipment.

### Respiratory Equipment


No specific requirements

### Skin protection

No specific requirements.


### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	-	-	EN374-2



### Eye protection

Type	Standards
Safety glasses with side shields.	EN166



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Liquid

#### Colour

Green

**Odour / Odour threshold**

Perfume

**pH**

5

**Density (g/cm<sup>3</sup>)**

0.98

**Kinematic viscosity**

Testing not relevant or not possible due to the nature of the product.

**Particle characteristics**

Does not apply to liquids.

**Phase changes**

**Melting point/Freezing point (°C)**

Testing not relevant or not possible due to the nature of the product.

**Softening point/range (waxes and pastes) (°C)**

Does not apply to liquids.

**Boiling point (°C)**

Testing not relevant or not possible due to the nature of the product.

**Vapour pressure**

Testing not relevant or not possible due to the nature of the product.

**Relative vapour density**

Testing not relevant or not possible due to the nature of the product.

**Decomposition temperature (°C)**

Testing not relevant or not possible due to the nature of the product.

**Data on fire and explosion hazards**

**Flash point (°C)**

42

**Auto-Ignition (°C)**

Testing not relevant or not possible due to the nature of the product.

**Flammability (°C)**

Testing not relevant or not possible due to the nature of the product.

**Lower and upper explosion limit (% v/v)**

Testing not relevant or not possible due to the nature of the product.

**Solubility**

**Solubility in water**

Completely soluble

**n-octanol/water coefficient**

Testing not relevant or not possible due to the nature of the product.

**Solubility in fat (g/L)**

Testing not relevant or not possible due to the nature of the product.

**9.2. Other information**

**Other physical and chemical parameters**

No data available.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

The product is stable under the conditions, noted in section 7 "Handling and storage".

**10.3. Possibility of hazardous reactions**

None known.

**10.4. Conditions to avoid**

Avoid static electricity.

**10.5. Incompatible materials**

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

**10.6. Hazardous decomposition products**

The product is not degraded when used as specified in section 1.



## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/substance	propan-2-ol
Test method	OECD 401
Species	Rat
Route of exposure	Oral
Test	LD50
Result	5840 mg/kg
Other information	

Product/substance	propan-2-ol
Test method	OECD 403
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	>25 mg/L
Other information	

Product/substance	propan-2-ol
Test method	OECD 402
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	13900 mg/kg
Other information	

Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	>5000 mg/kg
Other information	

Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	9510 mg/kg
Other information	

Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	3.35 mg/L
Other information	

Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Rat

Route of exposure	Oral
Test	LD50
Result	>2000 mg/kg
Other information	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	2764 mg/kg
Other information	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	>29 ppm
Other information	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Mouse
Route of exposure	Oral
Test	LD50
Result	2410 mg/kg
Other information	
Product/substance	propane-1,2-diol
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	22000 mg/kg
Other information	
Product/substance	propane-1,2-diol
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	>2000 mg/kg
Other information	
Product/substance	propane-1,2-diol
Test method	
Species	Rabbit
Route of exposure	Inhalation
Test	LC50 (2 hours)
Result	>317042 mg/m <sup>3</sup>
Other information	
Product/substance	1,2-benzisothiazol-3(2H)-one

Test method  
 Species Rat  
 Route of exposure Dermal  
 Test LD50  
 Result >2000 mg/kg  
 Other information

Product/substance 1,2-benzisothiazol-3(2H)-one  
 Test method  
 Species Mouse  
 Route of exposure Oral  
 Test LD50  
 Result 1150 mg/kg  
 Other information

Product/substance 1,2-benzisothiazol-3(2H)-one  
 Test method  
 Species Rat  
 Route of exposure Oral  
 Test LD50  
 Result 597 mg/kg  
 Other information

Product/substance 1,2-benzisothiazol-3(2H)-one  
 Test method  
 Species Rat  
 Route of exposure Dermal  
 Test LD50  
 Result >2000 mg/kg engångsdos ·  
 Other information

Product/substance 1,2-benzisothiazol-3(2H)-one  
 Test method  
 Species Rat  
 Route of exposure Oral  
 Test LD50  
 Result 1020 mg/kg ·  
 Other information

### Skin corrosion/irritation

Product/substance 2-(2-butoxyethoxy)ethanol  
 Test method OECD 404  
 Species Rabbit  
 Duration  
 Result No adverse effect observed (Not irritating)  
 Other information

### Serious eye damage/irritation

Product/substance 2-(2-butoxyethoxy)ethanol  
 Test method OECD 404  
 Species Rabbit  
 Duration  
 Result Adverse effect observed (Irritating)

Other information

### Respiratory sensitisation

Based on available data, the classification criteria are not met.

### Skin sensitisation

Product/substance	2-(2-butoxyethoxy)ethanol
Test method	OECD 406
Species	Guinea pig
Result	No adverse effect observed (not sensitising)
Other information	

### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

### Carcinogenicity

Based on available data, the classification criteria are not met.

### Reproductive toxicity

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### Long term effects

None known.

### Endocrine disrupting properties

None known.

### Other information

propan-2-ol has been classified by IARC as a group 3 carcinogen.

## SECTION 12: Ecological information

### 12.1. Toxicity

Product/substance	propan-2-ol
Test method	
Species	Fish
Compartment	
Duration	96 hours
Test	LC50
Result	>100 mg/L
Other information	

Product/substance	propan-2-ol
Test method	
Species	Algae
Compartment	
Duration	8 d
Test	LOEC
Result	1000 mg/L
Other information	

Product/substance	propan-2-ol
Test method	
Species	Daphnia, Daphnia magna

Compartment	
Duration	48 hours
Test	LC50
Result	>100 mg/L
Other information	
<hr/>	
Product/substance	propan-2-ol
Test method	
Species	Algae
Compartment	
Duration	72 hours
Test	EC50
Result	>100 mg/L
Other information	
<hr/>	
Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Fish, <i>Poecilia reticulata</i>
Compartment	
Duration	96 hours
Test	LC50
Result	>1000 mg/L
Other information	
<hr/>	
Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Daphnia, <i>Daphnia magna</i>
Compartment	
Duration	48 hours
Test	EC50
Result	1919 mg/L
Other information	
<hr/>	
Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Daphnia, <i>Daphnia magna</i>
Compartment	
Duration	22 d
Test	NOEC
Result	0.5 mg/L
Other information	
<hr/>	
Product/substance	(2-methoxymethylethoxy)propanol
Test method	
Species	Algae, <i>Pseudokirchneriella subcapitata</i>
Compartment	
Duration	72 hours
Test	EC50
Result	>969 mg/L
Other information	
<hr/>	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Fish, <i>Leuciscus idus</i>

Compartment	
Duration	96 hours
Test	LC50
Result	>100 mg/L
Other information	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Algae, <i>Scenedesmus subspicatus</i>
Compartment	
Duration	96 hours
Test	EC50
Result	>100 mg/L
Other information	
Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Species	Daphnia, <i>Daphnia magna</i>
Compartment	
Duration	48 hours
Test	EC50
Result	>100 mg/L
Other information	
Product/substance	propane-1,2-diol
Test method	
Species	Fish, <i>Oncorhynchus mykiss</i>
Compartment	
Duration	96 hours
Test	LC50
Result	40613 mg/L
Other information	
Product/substance	propane-1,2-diol
Test method	
Species	Daphnia, <i>Ceriodaphnia dubia</i>
Compartment	
Duration	48 hours
Test	EC50
Result	18340 mg/L
Other information	
Product/substance	propane-1,2-diol
Test method	
Species	Algae, <i>Pseudokirchneriella subcapitata</i>
Compartment	
Duration	96 hours
Test	ErC50
Result	19000 mg/L
Other information	
Product/substance	1,2-benzisothiazol-3(2H)-one
Test method	
Species	Daphnia, <i>Daphnia magna</i>

Compartment  
 Duration 48 hours  
 Test EC50  
 Result 2.44 mg/L  
 Other information

Product/substance 1,2-benzisothiazol-3(2H)-one  
 Test method  
 Species Fish  
 Compartment  
 Duration 96 hours  
 Test LC50  
 Result 0.74 mg/L  
 Other information

### 12.2. Persistence and degradability

Product/substance propan-2-ol  
 Biodegradable Yes  
 Test method  
 Result

Product/substance (2-methoxymethylethoxy)propanol  
 Biodegradable Yes  
 Test method OECD 301 F  
 Result 75%

Product/substance 2-(2-butoxyethoxy)ethanol  
 Biodegradable Yes  
 Test method OECD 301 E  
 Result 100%

Product/substance propane-1,2-diol  
 Biodegradable Yes  
 Test method OECD 301 F  
 Result 81%

### 12.3. Bioaccumulative potential

Product/substance propan-2-ol  
 Test method  
 Potential bioaccumulation No  
 LogPow 0.0500  
 BCF No data available.  
 Other information

Product/substance (2-methoxymethylethoxy)propanol  
 Test method  
 Potential bioaccumulation No  
 LogPow 0.0060  
 BCF No data available.  
 Other information

Product/substance	2-(2-butoxyethoxy)ethanol
Test method	
Potential bioaccumulation	No
LogPow	1.0000
BCF	No data available.
Other information	

Product/substance	propane-1,2-diol
Test method	
Potential bioaccumulation	No
LogPow	-1.0700
BCF	No data available.
Other information	

Product/substance	1,2-benzisothiazol-3(2H)-one
Test method	
Potential bioaccumulation	No
LogPow	1.4
BCF	No data available.
Other information	

#### 12.4. Mobility in soil

(2-methoxymethylethoxy)propanol  
LogKoc = 0.28, High mobility potential.

#### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

#### 12.6. Endocrine disrupting properties

None known.

#### 12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

### SECTION 13: Disposal considerations

#### Waste treatment methods

Product is covered by the regulations on hazardous waste.

To the extent the material has not been subject to regular tests of peroxide formation the waste shall be treated as explosive waste.

HP 3 - Flammable

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

#### EWC code

07 06

04\*

Other organic solvents, washing liquids and mother liquors

#### Specific labelling




Not applicable.

#### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

### SECTION 14: Transport information



	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es) Labels: 3 Classification code:	14.4 PG*	14.5 Env**	Other information
ADR	UN1993	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)	Class: 3 Labels: 3 Classification code: F1 	III	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1993	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)	Class: 3 Labels: 3 Classification code: F1 	III	No	Limited quantities: 5 L EmS: F-E S-E See below for additional information.
IATA	UN1993	FLAMMABLE LIQUID, N.O.S. (propan-2-ol)	Class: 3 Labels: 3 Classification code: F1 	III	No	See below for additional information.

\* Packing group  
\*\* Environmental hazards

**Additional information**  
ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.  
IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.  
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.  
This product is within scope of the regulations of transport of dangerous goods.

**14.6. Special precautions for user**  
Not applicable.

**14.7. Maritime transport in bulk according to IMO instruments**  
No data available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

None known.

#### Demands for specific education

No specific requirements.

#### SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

#### REACH, Annex XVII

2-(2-butoxyethoxy)ethanol is subject to restrictions, UK-REACH annex XVII (entry 55).

#### Additional information

Not applicable.

#### Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

### 15.2. Chemical safety assessment

No

## SECTION 16: Other information

### Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H302, Harmful if swallowed.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

H400, Very toxic to aquatic life.

H411, Toxic to aquatic life with long lasting effects.

### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

### Additional information

The classification of the substance/mixture in regard of environmental hazards are in accordance with the

calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.  
The classification of the mixture in regard to physical hazards has been based on experimental data.

**The safety data sheet is validated by**

ÅM

**Other**

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en