

Page 1 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Ditec Medium Cut Art.: 1003A alt. 1003A250

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture: Polish

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Ditec International AB Ahrenbergs Brygga 32 S-195 61 ARLANDASTAD (Stockholm) phone: +46 10 344 74 50 info@ditecinternational.com www.ditecinternational.com

1.4 Emergency telephone number Emergency information services / official advisory body:

Phone number for emergencies: 999 or 112. The numbers are available 24/7.

Telephone number of the company in case of emergencies:

+46 10 344 74 50 (Ditec International)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH066-Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Page 2 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %). The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

01-2119487078-27-XXXX
232-455-8
8042-47-5
10-<25
Asp. Tox. 1, H304

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	918-481-9
CAS	(64742-48-9)
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-	EUH066
factors	Asp. Tox. 1, H304

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

Page 3 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. **4.3 Indication of any immediate medical attention and special treatment needed** Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher Cool container at risk with water.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of sulphur Oxides of nitrogen Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation. Avoid build up of dust. Avoid contact with eyes or skin. Page 4 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing. Store at room temperature. Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Hydrocarbons, C	10-C13, n-alkanes, isoalkanes,	cyclics, <2% aromatics	
WEL-TWA: 800 mg/m3		WEL-STEL:		
Monitoring procedures:		Draeger - Hydrocarbons 0,1%/c		
		Draeger - Hydrocarbons 2/a (81	03 581)	
	- (Compur - KITA-187 S (551 174)		
BMGV:				OEL acc. to RCP-
			method, paragraphs 8	84-87, EH40)
Chemical Name	Hvdrocarbons, C	10-C13, n-alkanes, isoalkanes,	cvclics. <2% aromatics	
OELV-8h: 100 ppm (573 mg/m3	3) ("Stoddard	OELV-15min:		
solvent", [White spirit])	, (
Monitoring procedures:	- [Draeger - Hydrocarbons 0,1%/c	(81 03 571)	
		Draeger - Hydrocarbons 2/a (81		
		Compur - KITA-187 S (551 174)		
BLV:		· · · · · ·	Other information: -	
Chemical Name	Glycerine			
WEL-TWA: 10 mg/m3 (mist)		WEL-STEL:		
Monitoring procedures:	-			1
BMGV:			Other information: -	
Chemical Name	Aluminium oxide			
Chemical Name WEL-TWA: 10 mg/m3 (total inha	Aluminium oxide al. dust). 4	WEL-STEL:		
WEL-TWA: 10 mg/m3 (total inha	al. dust), 4	WEL-STEL:		
WEL-TWA: 10 mg/m3 (total inhamg/m3 (resp. dust) (aluminium ox	al. dust), 4 (ides)	WEL-STEL:		
WEL-TWA: 10 mg/m3 (total inha	al. dust), 4 (ides)		Other information:	
WEL-TWA: 10 mg/m3 (total inha mg/m3 (resp. dust) (aluminium ox Monitoring procedures: BMGV:	al. dust), 4 kides) -		Other information:	
WEL-TWA: 10 mg/m3 (total inha mg/m3 (resp. dust) (aluminium ox Monitoring procedures: BMGV:	al. dust), 4 kides) - Aluminium oxide		Other information:	
WEL-TWA: 10 mg/m3 (total inha mg/m3 (resp. dust) (aluminium ox Monitoring procedures: BMGV: ^(R) Chemical Name OELV-8h: 4 mg/m3 (respirable of	al. dust), 4 tides) Aluminium oxide dust), 10 mg/m3		Other information:	
WEL-TWA: 10 mg/m3 (total inha mg/m3 (resp. dust) (aluminium ox Monitoring procedures: BMGV: © Chemical Name OELV-8h: 4 mg/m3 (respirable of (total inhalable dust) (Aluminium of	al. dust), 4 kides) Aluminium oxide dust), 10 mg/m3 oxides)		Other information: -	
WEL-TWA: 10 mg/m3 (total inha mg/m3 (resp. dust) (aluminium ox Monitoring procedures: BMGV: ^(R) Chemical Name OELV-8h: 4 mg/m3 (respirable of	al. dust), 4 kides) Aluminium oxide dust), 10 mg/m3 oxides)	OELV-15min:		
WEL-TWA: 10 mg/m3 (total inhamg/m3 (resp. dust) (aluminium ox Monitoring procedures: BMGV: Re Chemical Name OELV-8h: 4 mg/m3 (respirable of (total inhalable dust) (Aluminium of Monitoring procedures: BLV:	al. dust), 4 kides) Aluminium oxide dust), 10 mg/m3 oxides)	OELV-15min:		
WEL-TWA: 10 mg/m3 (total inhamg/m3 (resp. dust) (aluminium ox Monitoring procedures: BMGV: © Chemical Name OELV-8h: 4 mg/m3 (respirable of (total inhalable dust) (Aluminium of Monitoring procedures: BLV: © Chemical Name	al. dust), 4 tides) Aluminium oxide dust), 10 mg/m3 oxides) Oil mist, mineral	 OELV-15min:		
WEL-TWA: 10 mg/m3 (total inhimg/m3 (resp. dust) (aluminium ox Monitoring procedures: BMGV: © Chemical Name OELV-8h: 4 mg/m3 (respirable of (total inhalable dust) (Aluminium of Monitoring procedures: BLV: © Chemical Name WEL-TWA: 5 mg/m3 (Mineral of	al. dust), 4 tides) Aluminium oxide dust), 10 mg/m3 oxides) Oil mist, mineral	 OELV-15min:		
WEL-TWA: 10 mg/m3 (total inha mg/m3 (resp. dust) (aluminium ox Monitoring procedures: BMGV: © Chemical Name OELV-8h: 4 mg/m3 (respirable of (total inhalable dust) (Aluminium of Monitoring procedures: BLV: © Chemical Name WEL-TWA: 5 mg/m3 (Mineral of metal working fluids, ACGIH)	al. dust), 4 tides) Aluminium oxide dust), 10 mg/m3 oxides) Oil mist, mineral il, excluding	 OELV-15min: WEL-STEL:	Other information:	
WEL-TWA: 10 mg/m3 (total inhimg/m3 (resp. dust) (aluminium ox Monitoring procedures: BMGV: © Chemical Name OELV-8h: 4 mg/m3 (respirable of (total inhalable dust) (Aluminium of Monitoring procedures: BLV: © Chemical Name WEL-TWA: 5 mg/m3 (Mineral of	al. dust), 4 tides) Aluminium oxide dust), 10 mg/m3 oxides) Oil mist, mineral il, excluding	 OELV-15min:	Other information: -	
WEL-TWA: 10 mg/m3 (total inhimg/m3 (resp. dust) (aluminium ox Monitoring procedures: BMGV: Chemical Name OELV-8h: 4 mg/m3 (respirable of (total inhalable dust) (Aluminium of Monitoring procedures: BLV: Cell Chemical Name WEL-TWA: 5 mg/m3 (Mineral of metal working fluids, ACGIH) Monitoring procedures: BMGV:	al. dust), 4 tides) Aluminium oxide dust), 10 mg/m3 oxides) Oil mist, mineral il, excluding - [OELV-15min: WEL-STEL:	Other information: -	
WEL-TWA: 10 mg/m3 (total inhimg/m3 (resp. dust) (aluminium ox Monitoring procedures: BMGV: Chemical Name OELV-8h: 4 mg/m3 (respirable of (total inhalable dust) (Aluminium of Monitoring procedures: BLV: Chemical Name WEL-TWA: 5 mg/m3 (Mineral of metal working fluids, ACGIH) Monitoring procedures:	al. dust), 4 tides) Aluminium oxide dust), 10 mg/m3 oxides) Oil mist, mineral il, excluding	 OELV-15min: WEL-STEL:	Other information: -	

Page 5 of 18 Safety data sheet according to Regulation (EC) No 1907/2 Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250	2006, Annex II
OELV-8h: 5 mg/m3 (Mineral oil, pure, highly & OE	LV-15min:

OELV-8h: 5 mg/m3 (Mineral oil, pure, highly &	OELV-15min:	
severely refined (inhalable))		
Monitoring procedures: -	Draeger - Oil Mist 1/a (67 33 031)	
BLV:	Other information:	

White mineral oil (Natur	al oil)					
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	92	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	35	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	40	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	160	mg/m3	
Workers / employees	Human - dermal	Long term, local effects	DNEL	220	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	220	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	160	mg/m3	

Area of application	Exposure route / Environmental	Effect on health	Descripto r	Value	Unit	Note
	compartment					
Consumer	Human - oral	Long term, systemic effects	DNEL	300	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	900	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg	

Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	0,885	mg/l	
	Environment - marine		PNEC	0,088	mg/l	
	Environment - sewage treatment plant		PNEC	1000	mg/l	
	Environment - sediment, freshwater		PNEC	3,3	mg/kg dw	
	Environment - sediment, marine		PNEC	0,33	mg/kg dw	
	Environment - soil		PNEC	0,141	mg/kg dw	
	Environment - water, sporadic (intermittent) release		PNEC	8,85	mg/l	
Consumer	Human - inhalation	Long term, local effects	DNEL	33	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	229	mg/kg bw/day	

Page 6 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250

Workers / employees	Human - inhalation	Long term, local effects	DNEL	56	mg/m3	

Aluminium oxide						
Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - sewage		PNEC	20	mg/l	
	treatment plant					
Industrial	Human - inhalation	Long term	DNEL	3	mg/m3	
Commercial	Human - inhalation	Long term	DNEL	3	mg/m3	
Consumer	Human - oral	Long term	DNEL	6,22	mg/kg	
					bw/day	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |

OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU. (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BLV = Biological limit value |

Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average)

[9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |

OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period)

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

[8] = Short-term exposure limit value in relation to a reference period of 1 minute. (S.L.424.24), [9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24) |

BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Skin = Possibility of a significant uptake through the skin.

[11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences

Page 7 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250

that may arise in the presence of other sulphur compounds. (S.L.424.24), [12] = The mist is defined as the thoracic fraction. (S.L.424.24), [13] = Established in accordance with the Annex to Directive 91/322/EEC. (S.L.424.24), [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV. (S.L.424.24).

(EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and nonmetrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

If applicable

Protective Neoprene® / polychloroprene gloves (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Filter A P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed. Page 8 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	White
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	There is no information available on this parameter.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	There is no information available on this parameter.
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	8
Kinematic viscosity:	>20,5 mm2/s (40°C)
Solubility:	There is no information available on this parameter.
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	1,05 g/ml
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.
9.2 Other information	
Explosives:	Product is not explosive.
Oxidising liquids:	No

SECTION 10: Stability and reactivity

10.1 Reactivity The product has not been tested. 10.2 Chemical stability Stable with proper storage and handling. 10.3 Possibility of hazardous reactions No dangerous reactions are known. 10.4 Conditions to avoid None known 10.5 Incompatible materials Avoid contact with strong oxidizing agents. 10.6 Hazardous decomposition products No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						

Page 9 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250

Respiratory or skin		n.d.a.
sensitisation:		
Germ cell mutagenicity:		n.d.a.
Carcinogenicity:		n.d.a.
Reproductive toxicity:		n.d.a.
Specific target organ toxicity -		n.d.a.
single exposure (STOT-SE):		
Specific target organ toxicity -		n.d.a.
repeated exposure (STOT-		
RE):		
Aspiration hazard:		n.d.a.
Symptoms:		n.d.a.

White mineral oil (Natural oil Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	NOLES
Acute toxicity, by oral route.	LD50	>5000	тід/кд	Ral	Oral Toxicity)	
Aquita taxiaity, by darmal	LD50	>2000		Rabbit	OECD 402 (Acute	
Acute toxicity, by dermal	LD50	>2000	mg/kg	Raddil		
route:	1.050	_		Det	Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat	OECD 403 (Acute	
				5	Inhalation Toxicity)	N I I I I I
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
<u> </u>					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact)
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	
Carcinogenicity:	NOAEL	>1200	mg/kg	Rat	OECD 453	Negative
	-		5.5		(Combined Chronic	- 3
					Toxicity/Carcinogenicit	
					y Studies)	
Reproductive toxicity:					OECD 415 (One-	Negative
Reproductive toxicity.					Generation	Negative
					Reproduction Toxicity	
					Study)	
Depreductive toxicity	NOAEL	>=1000		Rat	OECD 421	Negative
Reproductive toxicity:	NOAEL	>=1000	mg/kg	Ral		Negative
			bw/d		(Reproduction/Develop	
					mental Toxicity	
• • • • • • • • • • • • • • • • • • •				-	Screening Test)	
Specific target organ toxicity -	NOAEL	>1200	mg/kg	Rat	OECD 453	
repeated exposure (STOT-					(Combined Chronic	
RE):					Toxicity/Carcinogenicit	
					y Studies)	
Specific target organ toxicity -	NOAEL	>1200	mg/kg		OECD 452 (Chronic	
repeated exposure (STOT-					Toxicity Studies)	
RE):						
Aspiration hazard:						Asp. Tox. 1
Symptoms:						nausea and
						vomiting.
Specific target organ toxicity -	NOAEL	>2000	mg/kg	Rat	OECD 411	
repeated exposure (STOT-			3.13		(Subchronic Dermal	
RE), dermal:					Toxicity - 90-day	
					Study)	
Specific target organ toxicity -	NOAEL	1000	mg/kg	Rabbit	OECD 410 (Repeated	
repeated exposure (STOT-	NUALL	1000	ing/kg	Tabbit	Dose Dermal Toxicity -	
RE), dermal:		1			90-Day)	

Page 10 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250

Hydrocarbons, C10-C13, n-a						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
route:		- 2000			Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8	Rat	OECD 403 (Acute	Vapours
Acute toxicity, by initialation.	LOOU	20000	h	- Not	Inhalation Toxicity)	vapours
Acute toxicity, by inhalation:	LC50	>5	mg/m3/4	Rat	OECD 403 (Acute	Vapours,
Acute toxicity, by initialation.	2030		-	Rai	Inhalation Toxicity)	Analogous
			h		Initialation Toxicity)	
						conclusion
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.,
						Product
						removes fat.
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye					OECD 405 (Acute	Not irritant
damage/irritation:					Eye	Not initialit
damage/imation.					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:				Guinea pig		
				Colmonollo	Sensitisation)	contact)
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	<u> </u>
Germ cell mutagenicity:				Mouse	OECD 474	Negative,
					(Mammalian	Analogous
					Erythrocyte	conclusion
					Micronucleus Test)	
Carcinogenicity:					OECD 453	Negative,
					(Combined Chronic	Analogous
					Toxicity/Carcinogenicit	conclusion
					y Studies)	
Reproductive toxicity:		1			OECD 421	Negative,
					(Reproduction/Develop	Analogous
					mental Toxicity	conclusion
					Screening Test)	20
Reproductive toxicity:	NOAEC	>= 5220	mg/m3	Rat	OECD 414 (Prenatal	Negative,
		- 0220	ing/ino		Developmental	Analogous
					Toxicity Study)	conclusioninha
					TOXICITY Study)	
Chapilia target arrest tavisit	+					ation
Specific target organ toxicity -					OECD 408 (Repeated	No indications
repeated exposure (STOT-					Dose 90-Day Oral	of such an
RE):					Toxicity Study in	effect.,
					Rodents)	Analogous
						conclusion
Aspiration hazard:						Yes

Page 11 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250

Symptoms:	s, he dizzi Derr inflar Redu dryir skin. merr irrita	
	vom diarr lowe	sea and iting., hoea, er ominal pain

Endpoint LD50 LD50	Value >2000 >10000	Unit mg/kg mg/kg	Organism Rat Rabbit	Test method	Notes
LD50	>10000	mg/kg	Rabbit		
			Rabbit		
			Rabbit	IUCLID Chem. Data Sheet (ESIS)	Not irritant
			Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
			Guinea pig		Not sensitizising
			Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
NOAEL	2000	mg/kg/d			Negative
NOAEL	3,91	mg/l	Rat		14d
					Negative
					abdominal pain, drowsiness, diarrhoea, vomiting, headaches, mucous membrane irritation,
_				NOAEL 2000 mg/kg/d	Eye Irritation/Corrosion) Guinea pig Salmonella typhimurium OECD 471 (Bacterial Reverse Mutation Test) NOAEL 2000

Aluminium oxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by oral route:	NOAEL	30	mg/kg	Rat		Analogous
						conclusion
Acute toxicity, by inhalation:	NOAEC	70	mg/m3	Rat		subchronic
Acute toxicity, by inhalation:	LC50	7,6	mg/l/4h	Rat		Aerosol,
			_			Maximum
						achievable
						concentration.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	

Page 12 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250

Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig		Not sensitizising
sensitisation:						
Germ cell mutagenicity:					in vivo	Negative,
						Analogous
						conclusion
Symptoms:						constipation
Specific target organ toxicity -	LOAEL	70	mg/m3	Rat		Lung damage
repeated exposure (STOT-						
RE), inhalat.:						

11.2. Information on other hazards

Feinschleifpaste F5.01						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting						Does not apply
properties:						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).										
Feinschleifpaste F5.01										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to fish:							n.d.a.			
12.1. Toxicity to							n.d.a.			
daphnia:										
12.1. Toxicity to algae:							n.d.a.			
12.2. Persistence and							n.d.a.			
degradability:										
12.3. Bioaccumulative							n.d.a.			
potential:										
12.4. Mobility in soil:							n.d.a.			
12.5. Results of PBT							n.d.a.			
and vPvB assessment										
12.6. Endocrine							Does not apply			
disrupting properties:							to mixtures.			
12.7. Other adverse							No information			
effects:							available on			
							other adverse			
							effects on the			
							environment.			
Other information:							DOC-			
							elimination			
							degree(complex			
							ing organic			
							substance)>=			
							80%/28d: n.a.			
Other information:	AOX			%			According to			
							the recipe,			
							contains no			
							AOX.			
White mineral oil (Natu	White mineral oil (Natural oil)									

Page 13 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		28d	>60	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Biodegradable
12.7. Other adverse effects:						,	Product floats on the water surface.
12.1. Toxicity to daphnia:	EL50	21d	>1000	mg/l	Daphnia magna		
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Leuciscus idus	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	LC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	48h	>1000	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	31,3	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable
Toxicity to bacteria:	LC50		>1000	mg/l	activated sludge	,	
Toxicity to bacteria:	NOELR		>100	mg/l	Pseudomonas subspicata		

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,10	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,18	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

Page 14 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250

12.2. Persistence and degradability:		28d	80	%	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		5,5-7,2			
12.4. Mobility in soil:	Log Koc		>3			
12.5. Results of PBT and vPvB assessment						No PBT substance, No vPvB substance
12.7. Other adverse effects:						Product floats on the water surface.
Water solubility:			~10	mg/l		Slight

Glycerine Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:	BOD5		0,87	g/g			
12.2. Persistence and degradability:	COD		1,16	g/g			
12.1. Toxicity to fish:	LC50	96h	> 5000	mg/l	Carassius auratus		
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC5	72h	3200	mg/l			Entosiphon sulcatum
12.1. Toxicity to algae:	EC50		2900	mg/l	Chlorella vulgaris		
12.2. Persistence and degradability:		14d	63	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	
12.2. Persistence and degradability:	BOD/COD		>60	%			
12.2. Persistence and degradability:	BOD5/COD		> 50	%			
12.2. Persistence and degradability:	DOC		>70	%			Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-1,75			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC5	16h	> 10000	mg/l	Pseudomonas putida		

Aluminium oxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	218,6	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	NOEC/NOEL	48h	>0,135	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

Page 15 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250

12.1. Toxicity to daphnia:	EC50		>100	mg/l	Daphnia magna		
12.3. Bioaccumulative potential:							Not to be expected
12.1. Toxicity to algae:	EC50		>100	mg/l	Selenastrum capricornutum		
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=0,052	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Inorganic products cannot be eliminated from water through biological purification methods.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

12 01 09 machining emulsions and solutions free of halogens

12 01 20 spent grinding bodies and grinding materials containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General sta	atements
-------------	----------

14.1. UN number or ID number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.

Page 16 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001				
Valid from: 10.06.2022				
PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250				
Marine Pollutant:	n.a			
14.5. Environmental hazards:	Not applicable			
Transport by air (IATA)				
14.2. UN proper shipping name:				
14.3. Transport hazard class(es):	n.a.			
14.4. Packing group:	n.a.			
14.5. Environmental hazards:	Not applicable			
14.6. Special precautions for user				
Unless specified otherwise, general measures for safe transport must be followed.				
14.7. Maritime transport in bulk according to IMO instruments				
Non-dangerous material according to Transport Regulations.				
SECTION 15: Regulatory information				
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture				
Observe restrictions: General hygiene measures for the handling of chemicals are applicable.				

Directive 2010/75/EU (VOC):

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

n.a.

11,5 %

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways. EUH066 Repeated exposure may cause skin dryness or cracking.

Asp. Tox. — Aspiration hazard

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

Page 17 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250 AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BSEF The International Bromine Council bw body weight Chemical Abstracts Service CAS Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of CLP substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dw drv weight e.g. for example (abbreviation of Latin 'exempli gratia'), for instance Effect Concentration/Level of x % on reduction of the biomass (algae, plants) EbCx, EyCx, EbLx (x = 10, 50) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community European Inventory of Existing Commercial Chemical Substances EINECS ELINCS European List of Notified Chemical Substances ΕN **European Norms** EPA United States Environmental Protection Agency (United States of America) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) $ErCx, E\mu Cx, ErLx (x = 10, 50)$ et cetera etc. EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general aen. GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc octanol-water partition coefficient Kow IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive IUCLIDInternational Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available NIOSHNational Institute for Occupational Safety and Health (USA) No-longer-Polymer NLP NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org. OSHA Occupational Safety and Health Administration (USA) persistent, bioaccumulative and toxic PBT

Page 18 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 10.06.2022 / 0001 Replacing version dated / version: 10.06.2022 / 0001 Valid from: 10.06.2022 PDF print date: 10.06.2022 Ditec Medium Cut Art.: 1003A alt. 1003A250

PE Polyethylene PNEC Predicted No Effect Concentration ppm parts per million PVC Polyvinylchloride REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical REACH-IT List-No. identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Ditec International, Ahrenbergs brygga 32, S-195 61 ARLANDASTAD SWEDEN Tel.: +46 10 344 74 50