

SAFETY DATA SHEET



In accordance with 1907/2006 annex II and 1272/2008

(All references to EU regulations and directives are abbreviated into only the numeric term)

Issued 2026-08-21

Version number 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name	Ditec 4A
UFI:	0250-60NY-900V-NXS0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Car care products
-----------------	-------------------

1.3. Details of the supplier of the safety data sheet

Company	Ditec International AB Dragrännan 2 746 50 Bålsta Sweden
Telephone	+46 10 344 74 50
E-mail	info@ditecinternational.com

1.4. Emergency telephone number

Phone number for emergencies: 999 or 112. The numbers are available 24/7.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 2, H225

Eye Irrit. 2, H319

STOT SE 3, H336

(See section 16)

2.2. Label elements

Hazard pictogram



Signal word	Danger
-------------	--------

Hazard statements

H225	Highly flammable liquid and vapour
------	------------------------------------

H319	Causes serious eye irritation
------	-------------------------------

H336	May cause drowsiness or dizziness
------	-----------------------------------

Precautionary statements

P101	If medical advice is needed, have product container or label at hand
------	--

P102	Keep out of reach of children
------	-------------------------------

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
------	---

P271	Use only outdoors or in a well-ventilated area
------	--

P280	Wear eye protection
------	---------------------

P403+P235	Store in a well-ventilated place. Keep cool
-----------	---

P405	Store locked up
------	-----------------

P501	Dispose of contents and container to authorised waste disposal facility
------	---

Supplemental hazard information

Contains: PROPAN-2-OL

2.3. Other hazards

The product does not contain any substances $\geq 0,1\%$ that are assessed to be a PBT or a vPvB in accordance with Annex XIII of REACH (EC) No 1907/2006.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Note that the table shows known hazards of the ingredients in pure form. These hazards are reduced or eliminated when mixed or diluted, see Section 16d.

Constituent	Classification	Concentration
PROPAN-2-OL		
CAS No: 67-63-0 EC No: 200-661-7 Index No: 603-117-00-0 REACH: 01-2119457558-25	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225, H319, H336	30 - 45 %
ETHANOL		
CAS No: 64-17-5 EC No: 200-578-6 Index No: 603-002-00-5 REACH: 01-2119457610-43	Flam. Liq. 2, Eye Irrit. 2; H225, H319 <i>Specific concentration limits and acute toxicity estimates (ATE):</i> <i>Eye Irrit. 2, H319: C $\geq 50\%$</i>	15 - 25 %

Explanations to the classification and labelling of the ingredients are given in Section 16e. Official abbreviations are printed in normal font. Text in italics are specifications and/or complements used in the calculation of the classification of this mixture, see Section 16b.

SECTION 4: First aid measures

4.1. Description of first aid measures

Generally

In case of concern, or if symptoms occur, call a doctor/physician.

Upon breathing in

Bring the injured person out into fresh air. Give artificial respiration if breathing has stopped. If breathing is difficult let trained personnel administer oxygen. Let the injured person rest in a warm place with fresh air and seek medical advice immediately.

Upon eye contact

Remove contact lenses immediately if possible.

Rinse the eye for several minutes with lukewarm water. If irritation persists call a doctor/ophthalmologist.

Upon skin contact

Remove contaminated clothes.

Wash the skin with soap and water.

If symptoms occur, contact a physician.

Upon ingestion

Rinse nose, mouth and throat with water.

Drink a couple of glasses of water immediately.

DO NOT induce vomiting.

Contact a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Upon breathing in

May cause drowsiness or disorientation.

Irritation may occur.

Upon eye contact

Causes serious eye irritation.

Redness.

Smarting pain.

Upon skin contact

Irritation may occur.
May cause dry skin.

Upon ingestion

May cause irritation of mucous membranes, nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.
Upon contact with a doctor, make sure to have the label or this safety data sheet with you.

SECTION 5: Firefighting measures

5.1. Extinguishing media**Recommended extinguishing agents**

Extinguish with water mist, powder, carbon dioxide or alcoholresistant foam.

Unsuitable extinguishing agents

May not be extinguished with water dispersed under high pressure.

5.2. Special hazards arising from the substance or mixture

Produces fumes containing harmful gases (carbon monoxide and carbon dioxide) when burning, and, in case of incomplete combustion, aldehydes and other toxic, harmful, irritant or environmentally harmful substances.
Emits flammable vapours which may form an explosive mixture with air.

5.3. Advice for firefighters

Protective measures to be taken with regard to other materials at the scene of the fire.
In case of fire use proper breathing apparatus.
Wear full protective clothing.
Vapors are heavier than air and may spread along floors.
The containers should be moved away from the place of fire, if this can take place without risks.
Cool closed containers that were exposed to fire with water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Note the risk of ignition.
Avoid contact with skin and eyes.
Note, risk for formation of sparks due to static electricity.
Switch off power at the main switch. Do not use the power switch in the room where the spillage has occurred.
Use recommended safety equipment, see section 8.
Switch off equipment which has an exposed flame, glows, or has a heat source of some other kind.
Ensure good ventilation.
Keep unauthorized and unprotected people at a safe distance.
Use breathing apparatus when oxygen levels are low or unknown.

6.2. Environmental precautions

Avoid release to drains, soil or watercourses.
Prevent from entering sewers, basements and pits, or any place where gas accumulation could be dangerous.
Please contact involved authorities if unintended release occurs.

6.3. Methods and material for containment and cleaning up

Do NOT use tools emitting sparks when cleaning.
Absorb the liquid with an inert absorbent, vermiculite, for example. Collect the material for disposal at a waste disposal facility.
Ensure good ventilation after sanitation.

6.4. Reference to other sections

See section 8 and 13 for personal protection equipment and disposal considerations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Take the necessary preventive and protective measures for safe handling.
Do not inhale the product and avoid exposure to skin, eyes and clothing.
Work in order to avoid spillage. If spillage does occur, address it immediately in accordance with the directions specified in Section 6 of this safety data sheet.
Vapors are heavier than air and may spread along floors.
Open fire, hot items, sparks or other ignition sources must not be present in the environment used for handling this product.
The product may be electrostatically charged. Always ground the containers while transferring the contents from one container to another. Do not use tools that may cause sparks.
Store this product separately from food items and keep it out of the reach of children and pets.
Do not eat, drink or smoke in premises where this product is handled.
Wash your hands after using the product.
Remove contaminated clothes.
Wash contaminated clothing before reuse.
Keep away from incompatible products.
Use recommended safety equipment, see section 8.
Implement appropriate engineering controls if necessary, see Section 8.

7.2. Conditions for safe storage, including any incompatibilities

The product should be stored in a manner which prevents hazards to health and the environment. Avoid exposure to humans and animals and do not discharge the product in a sensitive environment.
Take the necessary preventive and protective measures for safe storage.
Keep out of reach for children.
To be stored away from food and animal fodder and away from devices or surfaces that are in contact with those items.
Store tightly, in original packaging.
Always use sealed and visibly labeled packages.
Store in containers made of stainless steel.
Store as flammable liquid.
Keep away from heat and sunlight.
Store in dry and cool area.
Store in a well-ventilated and locked place.
Do not store close to incompatible materials (see section 10.5).

7.3. Specific end use(s)

See identified uses in Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National limit values

PROPAN-2-OL

United Kingdom (EH40/2005)

Time-weighted-average exposure limit (TWA) 400 ppm / 999 mg/m³

Short term exposure limit (STEL) 500 ppm / 1250 mg/m³

ETHANOL

United Kingdom (EH40/2005)

Time-weighted-average exposure limit (TWA) 1000 ppm / 1920 mg/m³

**DNEL
PROPAN-2-OL**

	Type of exposure	Route of exposure	Value
Consumer	Chronic Systemic	Inhalation	89 mg/m ³
Worker	Chronic Systemic	Dermal	888 mg/kg
Worker	Chronic Systemic	Inhalation	500 mg/m ³
Consumer	Chronic Systemic	Oral	26 mg/kg
Consumer	Chronic Systemic	Dermal	319 mg/kg

ETHANOL

	Type of exposure	Route of exposure	Value
Consumer	Chronic Systemic	Inhalation	114 mg/m ³
Worker	Chronic Systemic	Dermal	343 mg/kg
Worker	Chronic Systemic	Inhalation	950 mg/m ³
Consumer	Chronic Systemic	Oral	87 mg/kg
Consumer	Chronic Systemic	Dermal	206 mg/kg

**PNEC
PROPAN-2-OL**

Environmental protection target	PNEC value
Fresh water	140.9 mg/l
Freshwater sediments	552 mg/kg
Marine water	140.9 mg/l
Marine sediments	552 mg/kg
Food chain	160 mg/kg dw
Microorganisms in sewage treatment	2251 mg/l
Soil (agricultural)	28 mg/kg
Intermittent	140.9 mg/L

ETHANOL

Environmental protection target	PNEC value
Fresh water	0.96 mg/L
Marine water	0.79 mg/L

8.2. Exposure controls

The risks posed by the product or its constituents must be considered in the task specific risk assessment, in accordance with current working environment legislation. The risk assessment should be reviewed regularly and updated if necessary.

8.2.1. Appropriate engineering controls

The ventilation in the workplace must ensure an air quality that meets the requirements of the current working environment legislation. Local exhaust ventilation should be used to remove airborne contaminants at the source. Emergency showers and eye-rinsing facilities must be available at the workplace.

8.2.2. Individual protection measures, such as personal protective equipment

Eye/face protection

Use protective glasses with tight seals according to standard EN166.

Skin protection

Use suitable protective clothing.

Use protective gloves fulfilling the standard EN374 if there is a risk of direct contact.

During continuous contact use gloves with a minimum breakthrough time of at least 240 minutes, preferably over 480 minutes.

The most suitable protective glove should be chosen in consultation with the glove supplier, taking into account the risk assessment for the specific task and the properties of the chemicals involved. Note that the breakthrough time of the material is affected by the duration of the exposure, temperature conditions, abrasion, etcetera.

Based on the chemical properties of the product, the following glove materials are recommended (EN 374):.

– Butyl rubber.

Respiratory protection

Use appropriate respiratory protective equipment in case of insufficient ventilation.

The most appropriate respiratory protective equipment should be decided in consultation with the appointed safety representative, taking into account the risk assessment for the specific task.

Based on the physical and chemical properties of the product, the following filter type(s) and/or filter combination(s) are recommended:.

– A/P2.

8.2.3. Environmental exposure controls

For limiting environmental exposure, see section 12.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(a) Physical state	liquid
	Form: liquid
(b) Colour	red
(c) Odour	like alcohol
(d) Melting point/freezing point	Not indicated
(e) Boiling point or initial boiling point and boiling range	82 °C
(f) Flammability	Not indicated
(g) Lower and upper explosion limit	Not indicated
(h) Flash point	≈20 °C
(i) Auto-ignition temperature	Not indicated
(j) Decomposition temperature	Not indicated
(k) pH	Not indicated
(l) Kinematic viscosity	Not indicated
(m) Solubility	Solubility in water: Soluble
(n) Partition coefficient n-octanol/water (log value)	Not indicated
(o) Vapour pressure	Not indicated
(p) Density and/or relative density	0.96 kg/L
(q) Relative vapour density	Not indicated
(r) Particle characteristics	Not indicated

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Not indicated

9.2.2. Other safety characteristics

Not indicated

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapour can create explosive mixtures with air.

10.2. Chemical stability

The product is stable at normal storage and handling conditions.

10.3. Possibility of hazardous reactions

May emit volatile, flammable vapours. Avoid handling close to heat or ignition sources.

10.4. Conditions to avoid

Avoid heat, sparks and open flames.

Protect from direct sunlight.

10.5. Incompatible materials

Avoid contact with:

Strong oxidizing agents.

Amines.

Aldehydes.

Alkanolamines .

Alkalis.

Strong acids.

10.6. Hazardous decomposition products

None under normal conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on possible health hazards are based on experience and / or toxicological properties of several components in the product.

Acute toxicity

The product is not classified as acutely toxic.

PROPAN-2-OL

LD50 rabbit 24h: 13900 mg/kg Dermally

LC50 rat 6h: > 25 mg/l Inhalation

LD50 rat 24h: 5840 mg/kg Orally

ETHANOL

LD50 rabbit 24h: > 2000 mg/kg Dermally

LD50 rat 24h: > 2000 mg/kg Orally

LC50 Mouse 4h: > 20 mg/L Inhalation

Skin corrosion/irritation

The product is not classified for skin corrosion/irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

The product is not classified as sensitising.

Germ cell mutagenicity

The product is not classified as mutagen.

Carcinogenicity

The product is not classified as carcinogenic.

Reproductive toxicity

The product is not classified as a reproductive toxicant.

STOT-single exposure

May cause drowsiness or disorientation.

STOT-repeated exposure

The product is not classified for specific organ toxicity after repeated exposure.

Aspiration hazard

The product is not classified as being toxic for aspiration.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No information is available.

11.2.2. Other information

Not indicated.

SECTION 12: Ecological information

12.1. Toxicity

The product is not to be labelled as a environmental hazard. However, it is not inconceivable that large emissions, or repeated small emissions, can have a harmful effect on the environment.

Prevent release on land, in water and drains.

PROPAN-2-OL

LC50 Fathead minnow (*Pimephales promelas*) 96h: 9640 - 10000 mg/l

LC50 Freshwater water flea (*Daphnia magna*) 48h: 2285 mg/L

EC50 Freshwater water flea (*Daphnia magna*) 48 h: 13299 mg/l

EC50 Algae 72 h: > 1000 mg/l

EC50 Freshwater water flea (*Daphnia magna*) 24h: 10000 mg/l

NOEC Algae 72h: > 1000 mg/l

NOEC Freshwater water flea (*Daphnia magna*) 21d: 100 mg/l

LC50 *Oryzias latipes* 96h: > 100 mg/l

LC50 Freshwater water flea (*Daphnia magna*) 24h: > 10000 mg/l

ETHANOL

EC50 Algae 72 h: > 100 mg/L

LC50 Fish 96h: > 100 mg/L

LC50 Freshwater water flea (*Daphnia magna*) 24h: > 100 mg/L

12.2. Persistence and degradability

The product contains certain components which are easily degradable.

12.3. Bioaccumulative potential

The product contains certain components which do not accumulate in nature.

12.4. Mobility in soil

The product is soluble in water.

12.5. Results of PBT and vPvB assessment

The product does not contain any substances $\geq 0,1\%$ that are assessed to be a PBT or a vPvB in accordance with Annex XIII of REACH (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No information is available.

12.7. Other adverse effects

No known effects or hazards.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste handling of the product

Avoid discharge into sewers.

Discarded products must be disposed of as hazardous waste in accordance with regulations.

Not completely emptied packaging can contain remnants of dangerous substances and should therefore be handled as hazardous waste according to the above. Completely emptied packaging can be recycled.

See directive 2008/98/EC on waste. Observe national or regional provisions on waste management.

Classification according to 2008/98/EC

Recommended LoW-code: 16 01 21 Hazardous components other than those mentioned in 16 01 07 to 16 01 11 and

SECTION 14: Transport information

Where not otherwise stated the information applies to all of the UN Model Regulations, i.e. ADR (road), RID (railway), ADN (inland waterways), IMDG (sea), and ICAO (IATA) (air).

14.1. UN number or ID number

1987

14.2. UN proper shipping name

ALCOHOLS, N.O.S. (PROPAN-2-OL, ETHANOL)

14.3. Transport hazard class(es)

Class

3: Flammable liquids

Classification code (ADR/RID)

F1: Flammable liquids having a flash-point of or below 60 °C

Subsidiary risk (IMDG)

No subsidiary risk according to IMDG

Labels



14.4. Packing group

Packing group II

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Tunnel restrictions

Tunnel category: D/E

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

14.8 Other transport information

Transport category: 2; Highest total quantity per transported unit 333 kg or liters

Stowage category B (IMDG)

Emergency Schedule (EmS) for FIRE (IMDG) F-E

Emergency Schedule (EmS) for SPILLAGE (IMDG) S-D

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Not indicated.

15.2. Chemical safety assessment

Assessment and chemical safety report in accordance with 1907/2006 Annex I has not yet been performed.

SECTION 16: Other information

16a. Indication of where changes have been made to the previous version of the safety data sheet

Revisions of this document

This is the first version

16b. Legend to abbreviations and acronyms used in the safety data sheet

Full texts for Hazard Class and Category Code mentioned in section 2 and 3

Flam. Liq. 2 Flammable liquids, Hazard Category 2 - Flam. Liq. 2, H225 - Highly flammable liquid and vapour

Eye Irrit. 2 Serious eye damage/eye irritation, Hazard Category 2 - Eye Irrit. 2, H319 - Causes serious eye irritation

STOT SE 3 Specific target organ toxicity — Single exposure, Hazard Category 3, Narcosis - STOT SE 3, H336 - May cause drowsiness or dizziness

Explanations of the abbreviations in Section 14

ADR European Agreement concerning the International Transport of Dangerous Goods by Road

RID Regulations concerning the International Transport of Dangerous Goods by Rail

IMDG International Maritime Dangerous Goods Code

ICAO International Civil Aviation Organization (ICAO, 999 University Street, Montreal, Quebec H3C 5H7, Canada)

IATA The International Air Transport Association

Tunnel restriction code: D/E; Transport by bulk or via tank: Passage forbidden through tunnels of category D and E, Other transportation means: Passage forbidden through tunnels of category E

Transport category: 2; Highest total quantity per transported unit 333 kg or liters

16c. Key literature references and sources for data

Sources for data

Primary data for the calculation of the hazards has preferentially been taken from the official European classification list, 1272/2008 Annex I, as updated to 2026-08-21.

Where such data was not available, alternative documentation used to establish the official classification was used, e.g. IUCLID (International Uniform Chemical Information Database). As a second alternative, information was used from reputable international chemical industries, and as a third alternative other available information was used, e.g. material safety data sheets from other suppliers or information from non-profit associations, where reliability of the source was assessed by expert opinion. If, in spite of this, reliable information could not be sourced, the hazards were assessed by expert opinions based on the known hazards of similar substances, and according to the principles in 1907/2006 and 1272/2008.

Full texts for Regulations mentioned in this Safety Data Sheet

- 1907/2006 REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC
- 1272/2008 REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006
- 2008/98/EC DIRECTIVE 2008/98/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 19 November 2008 on waste and repealing certain Directives

16d. Methods of evaluating information referred to in 1272/2008 Article 9 which was used for the purpose of classification

Hazard calculation for this mixture has been performed as a cumulative assessment with the aid of expert assessments in accordance with 1272/2008 Annex I, where all available information which may be significant to establishing the hazards of the mixture was assessed together, and in accordance with 1907/2006 Annex XI.

16e. List of relevant hazard statements and/or precautionary statements

Full texts for hazard statements mentioned in section 3

H225 Highly flammable liquid and vapour

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

16f. Advice on any training appropriate for workers to ensure protection of human health and the environment

Warning for misuse

This product can cause injuries if not used properly. The manufacturer, the distributor or the supplier are not responsible for adverse effects if the product is not handled in accordance with its intended use.

Other relevant information

Not indicated

Editorial information



This material safety data sheet has been prepared and checked by KemRisk®, KemRisk Sweden AB, Platensgatan 8, SE-582 20 Linköping, Sweden, www.kemrisk.se